

Features

- Miniature SIL package
- Single conversion FM Super-het using RF SAW and ceramic IF filtering at 10.7 MHz.
- (Image rejection 60dB)
- Incorporates AGC resulting in improved dynamic range
- Dynamic range better than 120dB
- Fully shielded
- Analogue, Digital and true RSSI outputs
- DATA RATES UP TO 128KBITS/S
- OPTIMAL RANGE 350m
- Operation on 433.92 MHz
- HIGH SENSITIVITY (-107 dBm)
- Very low current consumption (6mA)
- SINGLE 5V SUPPLY

Applications

- Telemetry systems
- Remote switching applications
- Paging systems
- Domestic and commercial security

General Description

The RS-MKR5 miniature receiver UHF radio module enables the implementation of a **reliable** telemetry link at data rates of up to 128Kbit/s when used with one of the compatible MK transmitter modules

Available for operation at 433.92 MHz these modules are able to receive at distances of up to 350metres.

Compatible Transmitter Modules

- RS-MKT5-XXX (see data sheet RS-MKT5)
- RS-MKT2 (see data sheet RS-MKT2)
The worlds smallest FM transmitter!

The receiver is based on the classical superhet single conversion architecture utilising a PLL xtal referenced oscillator which yields a highly stable IF frequency (10.7 MHz). This hence allows use of high Q bandpass filters offering excellent adjacent channel rejection and hence high interference Immunity.

The RS-MKR5 module will suit one-to-one and multi-node wireless links in applications including building and car security, remote industrial process monitoring and computer networking. Because of its small size and low power requirements, including a fast RSSI/CD, the module is ideal for use in portable battery powered wireless applications.

The module is highly suited for operation in harsh electrical environments where a reliable wireless link is essential.

Absolute Maximum Ratings: Receiver

Operating temperature:	-10°C to +55°C -40 to +80 deg C option available
Storage temperature:	-40°C to +100°C
Supply Voltage (pin 5)	7V
RF Input (pin 1)	+20 dBm (100mW)

Electrical Characteristics: Receiver (20 Kbits/sec version)

	pin	min.	typ.	max.	units	notes
DC LEVELS						
Supply voltage		4.5	5	5.5	V	
Supply current			6.0		mA	
Supply ripple		-	-	10	mV _{P-P}	
Data output high			=>4.0		V	
Data output low			<= 0.5		V	
RF						
RF sensitivity			-107		dBm	
IF Bandwidth			230		KHz	1
Initial frequency accuracy			±22		KHz	
Max R.F. input			20		dBm	
E.M.C.						
Spurious responses upto 1GHz			<60		dB	
LO leakage, conducted			<60		dBm	
LO leakage, radiated			<60		dBm	
Image rejection			60		dB	
DYNAMIC TIMING						
Power up to stable data <i>(With RF signal present)</i>			6		mS	2
Signal to stable data <i>(With power supply already on)</i>			5		mS	2
Power up to valid RSSI <i>(with RF signal present)</i>				1	mS	2
Mark:space ratio			50		%	
Bit rate		100		20000	bps	

Notes

- 1) IF bandwidth available down to 27KHz
- 2) Timings are to be confirmed

Connection Details




Figure 1: MKR5 Receiver

Pin Description

RF IN (*pin 1*)

50Ω RF input from antenna, connect using shortest possible route. This input is isolated from the internal circuit using the air gap of the front end SAW RF filter.

RF GND (*pin 2*)

RF ground connection, preferably connected to a solid ground plane.

RSSI / Carrier Detect (*pin 3*)

The Received Signal Strength Indicator provides a DC output voltage proportional to the RF input signal. The amplitude of the RSSI voltage increases with increasing RF signal strength. A simple transistor interface can yield a carrier detect logic output.

Gnd (*pin 4*)

Connect to power supply ground

V_{CC} (*pin 5*)

+Ve supply pin. Operation from a 5V supply able to source 6mA at less than 10mV_{P-P} ripple.

AF (*pin 6*)

Audio frequency output

DATA OUT (*pin 7*)

CMOS compatible output. This may be used to drive external decoders.

Application Information

Antenna Design

The design and positioning of the antenna is as crucial as the module performance itself in achieving a good wireless system range. The following will assist the designer in maximising system performance.

The antenna should be kept as far away from sources of electrical interference as physically possible. If necessary, additional power line decoupling capacitors should be placed close to the module.

The antenna 'hot end' should be kept clear of any objects, especially any metal as this can severely restrict the efficiency of the antenna to receive power. Any earth planes restricting the radiation path to the antenna will also have the same effect.

Best range is achieved with either a straight piece of wire, rod or PCB track @ ¼ wavelength (15.5cm @ 433.92MHz). Further range may be achieved if the ¼ wave antenna is placed perpendicular in the middle of a solid earth plane measuring at least 16cm radius. In this case, the antenna should be connected to the module via some 50 ohm characteristic impedance coax.




Figure 2: Antenna Configurations To Be Used With The MK receiver Module

Application Circuit

The application circuit shows how the RS-MKR5 Receiver can easily be integrated into a system to form a wireless link.




Figure 3: MK Receiver Application Circuit

RSSI Values

The RS-MKR5 RSSI output provides a DC output proportional to the RF input signal. The table below shows the typical RSSI value depending on the RF signal strength.

RF Signal Strength / dBm	RSSI / V
-120	1,35
-110	1,41
-100	1,57
-90	1,79
-80	1,8
-70	1,8
-60	2,15
-50	2,45
-40	2,58
-30	2,59
-20	2,59

Note that the region between -90 to -70 is with the receiver agc operating.

If required, a receiver version with agc disabled can be provided as a factory pre-set option. This would linearise the RSSI curve

Mechanical Dimensions




Figure 4: MKR5 Receiver

Ordering Information

Standard Product;

Part No	Description
RS-MKR5-434-20	20 Kbits/sec FM Receiver 433.92MHz
RS-MKR5-434-64	64 Kbits/sec FM Receiver 433.92 MHz
RS-MKR5-434-128	128 Kbits/sec FM receiver 433.92 MHz
RS-MKR5A-434	Pin compatible AM version receiver

Please consult our sales department for further information.

Round Solutions Ltd.
Niederlassung Deutschland
Zaunweg 4
D-63303 Dreieich
Tel. 06103 960510
Fax. 06103 960509

www.roundsolutions.com
info@roundsolutions.com